



|                |
|----------------|
| Catalog Number |
| Notes          |
| Type           |

Contractor Select™

# IC20 LEDT24

5" Housing for LED Retrofit Trims



The Juno® 5-inch quick connect LED housing for use with Juno retrofit LED trim modules offers an energy-efficient, Air-Loc® sealed housing that stops ex-filtration and infiltration of air, reducing heating and cooling costs without extra gaskets. The IC-rated housing can also be completely covered with insulation.

**FEATURES:**

- Features non-screw base 120V plug-in quick connector
- Compatible with Juno retrofit LED trim modules
- Can be used to comply with Title 24, JA8 high efficacy light source requirements



| Catalog Number | UPC          | Description   | Socket                      | Voltage | Pallet qty. |
|----------------|--------------|---|-----------------------------|---------|-------------|
| IC20 LEDT24    | 661209421517 | 5" New Construction IC Housing for LED Retrofit Trims | Quick Connector (No Socket) | 120V    | 120         |



## Specifications

### ELECTRONIC CONNECTIONS:

Features non-screw base 120V plug-in connector • Compatible with Juno retrofit LED trim modules.

### LABELS:

U.L. listed for U.S. and Canada for through-branch wiring and damp locations • Meets high efficacy requirements of California T24.

### TESTING:

All reports are based on published industry procedures; field performance may differ from laboratory performance.

### REAL NAIL® BAR HANGERS:

Telescoping, Real Nail® 3 system covered under US Patent D552,969 permits quick placement of housing anywhere within 24" O.C. joists or suspended ceilings. Integral T-bar notch and clip secures housing in suspended ceiling grid –no accessory clips required • 24" expansion stop allows quick placement of fixture in standard grid spacing • Bars scored in two locations for fast, clean breaking, allowing housing installation in tight applications • Bars captive to mounting frame • Edgemounted for extra strength • Captive bugle-headed ring shanknail for quick one-step installation and easy removal with clawhammer for fixture relocation • Quick-Loc slot (location identified on the mounting frame) and oversized locking set screw lock fixture in position • Bar hanger foot contoured to align to bottom of construction joist • Alternate mounting holes included.

### JUNCTION BOX:

Pre-wired junction box provided with (5) 1/2" and (1) 3/4" knockouts, (4) Non-metallic sheathed cable connectors and ground wire, U.L. listed/CSA certified for through-branch wiring, maximum 8 No. 12 AWG 90° C branch circuit conductors (4 in, 4 out) • Junction box provided with removable access plates • Knockouts equipped with pryout slots.

### HOUSING:

IC housing, .032" aluminum sealed for Air-Loc Compliance • 22-gauge die-formed galvanized steel mounting frame • Rough-in section (junction box, mounting frame, housing and bar hangers) fully assembled for ease of installation • Sight lines embossed on mounting frame to allow for easy viewing when aligning fixtures • Housing is vertically adjustable to accommodate up to a 1" ceiling thickness.

### WARRANTY:

1-year limited warranty. Complete warranty terms located at:

[www.acuitybrands.com/CustomerResources/Terms\\_and\\_conditions.aspx](http://www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx)

**Note:** Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications subject to change without notice.

## Dimensions

